

A301-150W(N) SPEC

ITEMS	DC12V	DC24V
OUTPUT POWER	100W CONTINUE 150W (30 MIN) 200W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10-15V	DC 20-30V
INPUT FULL LOAD CURRENT	15A	10A
OUTPUT VOLTAGE	AC 100V,110V,120V,220V,230V,240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
USB OUTPUT POWER	DC5V 500mA	DC5V 300mA
LOW VOLTAGE INPUT SHUTDOWN	DC 10+/- 0.5V	DC 19.5 +/- 0.8V
HIGH VOLTAGE INPUT SHUTDOWN	DC 15 +/- 0.5V	DC 30 +/- 0.8V
STANDBY CURRENT	0.25A	0.2A
EFFICIENCY	90%	
THERMAL PROTECT	60 +/- 0.5℃	
COOLING	BY AIR CONVECTION	
PROTECTIONS	※SOFT START ※OUTPUT SHORT : SHUTDOWN ※INPUT POLARITY REVERSE : BY FUSE ※HIGH VOLTAGE INPUT :SHUTDOWN ※LOW VOLTAGE INPUT : SHUTDOWN ※OVERLOAD : SHUTDOWN ※OVERTEMPERTURE : SHUTDOWN ※BATTERY LOW : SHUTDOWN ※TROUBLE DISPLAY : LED	
FUSE	15A	10A
AC OUTLET	ONE AC OUTLET	
SIZE(L*W*H)	φ 66*150 mm	
WEIGHT	0.43 kgs	

